

Certificate

of Conformity

This certifies that below described product(s) of the company:

SUNERG SOLAR SRL

Via Donino Donini, 51

06012 Loc. Cinquemiglia - Citta di Castello (PG)

comply to the essential requirements of the following standards

Description of product(s)
(details see Annex):

Crystalline Silicon Terrestrial Photovoltaic (PV) Modules

Certification program:

P12-VA-01 Rev. 17 / 09.20

Certification fundamental(s):

EN IEC 61730-1:2018, EN IEC 61730-2:2018

This certificate of conformity is based on the evaluation of samples of the product. It does not imply an assessment of the production and it does not permit the use of a mark of conformity or of a safety mark of TÜV NORD CERT GmbH.

The company may use this certificate as a basis of compliance with 2014/35/EU - low voltage directive, together with EU declaration of conformity (DoC) issued by the company. The CE marking may be affixed on the product if all relevant and effective directives and requirements are complied with, under full responsibility of the company.

Registration no.: 44 799 26 406749 - 427

Report no.: 492013177.004

File no.: PVP09184/26P-001

Essen, 2026-10-15

Certification Body - Consumer Products

TÜV NORD CERT GmbH

Am TÜV 1, 45307 Essen, Germany

tuev-nord-cert.de | prodcert@tuev-nord.de

Please also pay attention to the information stated overleaf.

TÜV®



Visit our database to
verify the validity of
this certificate.

Annex

to certificate registration no. 44 799 26 406749 – 427

Description of product(s):

Module types:

Double Glass PV Modules with 182 x 91 / 91.875 mm TOPCon Bifacial Mono Solar Cells:

156 cells: XMT1xxxCBDW (xxx = 605 - 645, in increment of 5)
 156 cells: XMT1xxxCBDBW (xxx = 605 - 645, in increment of 5)
 156 cells: XMT1xxxCBDBB (xxx = 605 - 645, in increment of 5)
 156 cells: XMT1xxxCBDFW (xxx = 605 - 645, in increment of 5)
 156 cells: XMT1xxxCBDFBW (xxx = 605 - 645, in increment of 5)
 156 cells: XMT1xxxCBDFBB (xxx = 605 - 645, in increment of 5)
 144 cells: XMTG1xxxCBDW (xxx = 565 - 595, in increment of 5)
 144 cells: XMTG1xxxCBDBW (xxx = 565 - 595, in increment of 5)
 144 cells: XMTG1xxxCBDBB (xxx = 565 - 595, in increment of 5)
 144 cells: XMTG1xxxCBDFW (xxx = 565 - 595, in increment of 5)
 144 cells: XMTG1xxxCBDFBW (xxx = 565 - 595, in increment of 5)
 144 cells: XMTG1xxxCBDFBB (xxx = 565 - 595, in increment of 5)
 132 cells: XMTF1xxxCBDW (xxx = 520 - 545, in increment of 5)
 132 cells: XMTF1xxxCBDBW (xxx = 520 - 545, in increment of 5)
 132 cells: XMTF1xxxCBDBB (xxx = 520 - 545, in increment of 5)
 132 cells: XMTF1xxxCBDFW (xxx = 520 - 545, in increment of 5)
 132 cells: XMTF1xxxCBDFBW (xxx = 520 - 545, in increment of 5)
 132 cells: XMTF1xxxCBDFBB (xxx = 520 - 545, in increment of 5)
 120 cells: XMTE1xxxCBDW (xxx = 470 - 495, in increment of 5)
 120 cells: XMTE1xxxCBDBW (xxx = 470 - 495, in increment of 5)
 120 cells: XMTE1xxxCBDBB (xxx = 470 - 495, in increment of 5)
 120 cells: XMTE1xxxCBDFW (xxx = 470 - 495, in increment of 5)
 120 cells: XMTE1xxxCBDFBW (xxx = 470 - 495, in increment of 5)
 120 cells: XMTE1xxxCBDFBB (xxx = 470 - 495, in increment of 5)
 108 cells: XMTD1xxxCBDW (xxx = 425 - 445, in increment of 5)
 108 cells: XMTD1xxxCBDBW (xxx = 425 - 445, in increment of 5)
 108 cells: XMTD1xxxCBDBB (xxx = 425 - 445, in increment of 5)
 108 cells: XMTD1xxxCBDFW (xxx = 425 - 445, in increment of 5)
 108 cells: XMTD1xxxCBDFBW (xxx = 425 - 445, in increment of 5)
 108 cells: XMTD1xxxCBDFBB (xxx = 425 - 445, in increment of 5)
 Remark: xxx indicates rated output power generated from front side under STC

Maximum system voltage:

1500V

Essen, 2026-10-15

Certification Body - Consumer Products

TÜV NORD CERT GmbH

Am TÜV 1, 45307 Essen, Germany

tuev-nord-cert.de | prodcert@tuev-nord.de

Maximum overcurrent protection rating: 30A
 Electrical protection class: Class II
 Pollution degree: 1
 98th percentile module operating temperature (T₉₈): 70°C

Module types:

Double Glass PV Modules with 182 x 95.8 mm TOPCon Bifacial Mono Solar Cells:

144 cells: XMTG7xxxCBDW (xxx = 595 - 625, in increment of 5)
 144 cells: XMTG7xxxCBDBW (xxx = 595 - 625, in increment of 5)
 144 cells: XMTG7xxxCBDBB (xxx = 595 - 625, in increment of 5)
 144 cells: XMTG7xxxCBDFW (xxx = 595 - 625, in increment of 5)
 144 cells: XMTG7xxxCBDFBW (xxx = 595 - 625, in increment of 5)
 144 cells: XMTG7xxxCBDFBB (xxx = 595 - 625, in increment of 5)
 144 cells: XMTG7xxxCBDW (xxx = 595 - 625, in increment of 5)
 144 cells: XMTG7xxxCBDBW (xxx = 595 - 625, in increment of 5)
 144 cells: XMTG7xxxCBDBB (xxx = 595 - 625, in increment of 5)
 144 cells: XMTG7xxxCBDFW (xxx = 595 - 625, in increment of 5)
 144 cells: XMTG7xxxCBDFBW (xxx = 595 - 625, in increment of 5)
 144 cells: XMTG7xxxCBDFBB (xxx = 595 - 625, in increment of 5)
 132 cells: XMTF7xxxCBDW (xxx = 545 - 570, in increment of 5)
 132 cells: XMTF7xxxCBDBW (xxx = 545 - 570, in increment of 5)
 132 cells: XMTF7xxxCBDBB (xxx = 545 - 570, in increment of 5)
 132 cells: XMTF7xxxCBDFW (xxx = 545 - 570, in increment of 5)
 132 cells: XMTF7xxxCBDFBW (xxx = 545 - 570, in increment of 5)
 132 cells: XMTF7xxxCBDFBB (xxx = 545 - 570, in increment of 5)
 132 cells: XMTF7CBDW (xxx = 545 - 570, in increment of 5)
 132 cells: XMTF7CBDBW (xxx = 545 - 570, in increment of 5)
 132 cells: XMTF7CBDBB (xxx = 545 - 570, in increment of 5)
 132 cells: XMTF7CBDFW (xxx = 545 - 570, in increment of 5)
 132 cells: XMTF7CBDFBW (xxx = 545 - 570, in increment of 5)
 132 cells: XMTF7CBDFBB (xxx = 545 - 570, in increment of 5)
 120 cells: XMTE7xxxCBDW (xxx = 495 - 520, in increment of 5)
 120 cells: XMTE7xxxCBDBW (xxx = 495 - 520, in increment of 5)
 120 cells: XMTE7xxxCBDBB (xxx = 495 - 520, in increment of 5)
 120 cells: XMTE7xxxCBDFW (xxx = 495 - 520, in increment of 5)
 120 cells: XMTE7xxxCBDFBW (xxx = 495 - 520, in increment of 5)
 120 cells: XMTE7xxxCBDFBB (xxx = 495 - 520, in increment of 5)
 120 cells: XMTE7xxxCBDW (xxx = 495 - 520, in increment of 5)
 120 cells: XMTE7xxxCBDBW (xxx = 495 - 520, in increment of 5)
 120 cells: XMTE7xxxCBDBB (xxx = 495 - 520, in increment of 5)
 120 cells: XMTE7xxxCBDFW (xxx = 495 - 520, in increment of 5)
 120 cells: XMTE7xxxCBDFBW (xxx = 495 - 520, in increment of 5)
 120 cells: XMTE7xxxCBDFBB (xxx = 495 - 520, in increment of 5)
 108 cells: XMTD7xxxCBDW (xxx = 445 - 465, in increment of 5)
 108 cells: XMTD7xxxCBDBW (xxx = 445 - 465, in increment of 5)
 108 cells: XMTD7xxxCBDBB (xxx = 445 - 465, in increment of 5)

Essen, 2026-10-15

Certification Body - Consumer Products

TÜV NORD CERT GmbH

Am TÜV 1, 45307 Essen, Germany

tuev-nord-cert.de | prodcert@tuev-nord.de

108 cells: XMTD7xxxCBDFW (xxx = 445 - 465, in increment of 5)
 108 cells: XMTD7xxxCBDFBW (xxx = 445 - 465, in increment of 5)
 108 cells: XMTD7xxxCBDFBB (xxx = 445 - 465, in increment of 5)
 108 cells: XMTD7xxxCBDW (xxx = 445 - 465, in increment of 5)
 108 cells: XMTD7xxxCBDBW (xxx = 445 - 465, in increment of 5)
 108 cells: XMTD7xxxCBDBB (xxx = 445 - 465, in increment of 5)
 108 cells: XMTD7xxxCBDFW (xxx = 445 - 465, in increment of 5)
 108 cells: XMTD7xxxCBDFBW (xxx = 445 - 465, in increment of 5)
 108 cells: XMTD7xxxCBDFBB (xxx = 445 - 465, in increment of 5)
 Remark: xxx indicates rated output power generated from front side under STC

Maximum system voltage: 1500V
 Maximum overcurrent protection rating: 30A
 Electrical protection class: Class II
 Pollution degree: 1
 98th percentile module operating temperature (T₉₈): 70°C

Module types:

Double Glass PV Modules with 182 x 95.8 mm TOPCon Bifacial Mono Solar Cells and Colorful Glass:

108 cells: XMHTO6xxxBFDG (RR/CC/TT/AA/MM/LL/OO/SS/II) +H((xxx = 325-450, in increment of 5)

Remark: xxx indicates rated output power generated from front side under STC

Maximum system voltage: 1500V
 Maximum overcurrent protection rating: 30A
 Electrical protection class: Class II
 Pollution degree: 1
 98th percentile module operating temperature (T₉₈): 70°C

Module types:

Double Glass PV Modules with 182 x 84.6 mm TOPCon Bifacial Mono Solar Cells:

156 cells: XMTIOxxxCBDW (xxx = 565 - 595, in increment of 5)
 156 cells: XMTIOxxxCBDBW (xxx = 565 - 595, in increment of 5)
 156 cells: XMTIOxxxCBDBB (xxx = 565 - 595, in increment of 5)
 156 cells: XMTIOxxxCBDFW (xxx = 565 - 595, in increment of 5)
 156 cells: XMTIOxxxCBDFBW (xxx = 565 - 595, in increment of 5)
 156 cells: XMTIOxxxCBDFBB (xxx = 565 - 595, in increment of 5)
 Remark: xxx indicates rated output power generated from front side under STC

Maximum system voltage: 1500V
 Maximum overcurrent protection rating: 30A
 Electrical protection class: Class II
 Pollution degree: 1

Essen, 2026-10-15

Certification Body - Consumer Products

TÜV NORD CERT GmbH

Am TÜV 1, 45307 Essen, Germany

tuev-nord-cert.de | prodcert@tuev-nord.de

98th percentile module operating temperature (T₉₈): 70°C

Module types:

Double Glass PV Modules with 182 x 94 mm TOPCon Bifacial Mono Solar Cells:

144 cells: XMTG2xxxCBDW (xxx = 585 - 615, in increment of 5)
 144 cells: XMTG2xxxCBDBW (xxx = 585 - 615, in increment of 5)
 144 cells: XMTG2xxxCBDBB (xxx = 585 - 615, in increment of 5)
 144 cells: XMTG2xxxCBDFW (xxx = 585 - 615, in increment of 5)
 144 cells: XMTG2xxxCBDFBW (xxx = 585 - 615, in increment of 5)
 144 cells: XMTG2xxxCBDFBB (xxx = 585 - 615, in increment of 5)
 132 cells: MXTF2xxxCBDW (xxx = 535 - 560, in increment of 5)
 132 cells: MXTF2xxxCBDBW (xxx = 535 - 560, in increment of 5)
 132 cells: MXTF2xxxCBDBB (xxx = 535 - 560, in increment of 5)
 132 cells: MXTF2xxxCBDFW (xxx = 535 - 560, in increment of 5)
 132 cells: MXTF2xxxCBDFBW (xxx = 535 - 560, in increment of 5)
 132 cells: MXTF2xxxCBDFBB (xxx = 535 - 560, in increment of 5)
 120 cells: XMTE2xxx CBDW (xxx = 490 - 510, in increment of 5)
 120 cells: XMTE2xxx CBDBW (xxx = 490 - 510, in increment of 5)
 120 cells: XMTE2xxx CBDBB (xxx = 490 - 510, in increment of 5)
 120 cells: XMTE2xxx CBDFW (xxx = 490 - 510, in increment of 5)
 120 cells: XMTE2xxx CBDFBW (xxx = 490 - 510, in increment of 5)
 120 cells: XMTE2xxx CBDFBB (xxx = 490 - 510, in increment of 5)
 108 cells: XMTD2xxxCBDW (xxx = 440 - 460, in increment of 5)
 108 cells: XMTD2xxxCBDBW (xxx = 440 - 460, in increment of 5)
 108 cells: XMTD2xxxCBDBB (xxx = 440 - 460, in increment of 5)
 108 cells: XMTD2xxxCBDFW (xxx = 440 - 460, in increment of 5)
 108 cells: XMTD2xxxCBDFBW (xxx = 440 - 460, in increment of 5)
 108 cells: XMTD2xxxCBDFBB (xxx = 440 - 460, in increment of 5)
 Remark: xxx indicates rated output power generated from front side under STC

Maximum system voltage: 1500V
 Maximum overcurrent protection rating: 30A
 Electrical protection class: Class II
 Pollution degree: 1
 98th percentile module operating temperature (T₉₈): 70°C

Module types:

Double Glass PV Modules with 182 x 105 mm TOPCon Bifacial Mono Solar Cells:

132 cells: XMTF3xxxCBDW (xxx = 585 - 650, in increment of 5)
 132 cells: XMTF3xxxCBDBW (xxx = 585 - 650, in increment of 5)
 132 cells: XMTF3xxxCBDBB (xxx = 585 - 650, in increment of 5)
 132 cells: XMTF3xxxCBDFW (xxx = 585 - 650, in increment of 5)
 132 cells: XMTF3xxxCBDFBW (xxx = 585 - 650, in increment of 5)
 132 cells: XMTF3xxxCBDFBB (xxx = 585 - 650, in increment of 5)
 132 cells: XMTF5xxxCBDW (xxx = 585 - 650, in increment of 5)

Essen, 2026-10-15

Certification Body - Consumer Products

TÜV NORD CERT GmbH

Am TÜV 1, 45307 Essen, Germany

tuev-nord-cert.de | prodcert@tuev-nord.de

132 cells: XMTF5xxxCBDBW (xxx = 585 - 650, in increment of 5)
 132 cells: XMTF5xxxCBDBB (xxx = 585 - 650, in increment of 5)
 132 cells: XMTF5xxxCBDFW (xxx = 585 - 650, in increment of 5)
 132 cells: XMTF5xxxCBDFBW (xxx = 585 - 650, in increment of 5)
 120 cells: XMTE3xxxCBDBW (xxx = 530 - 590, in increment of 5)
 120 cells: XMTE3xxxCBDBB (xxx = 530 - 590, in increment of 5)
 120 cells: XMTE3xxxCBDFW (xxx = 530 - 590, in increment of 5)
 120 cells: XMTE3xxxCBDFBW (xxx = 530 - 590, in increment of 5)
 120 cells: XMTE5xxxCBDBW (xxx = 530 - 590, in increment of 5)
 120 cells: XMTE5xxxCBDBB (xxx = 530 - 590, in increment of 5)
 120 cells: XMTE5xxxCBDFW (xxx = 530 - 590, in increment of 5)
 120 cells: XMTE5xxxCBDFBW (xxx = 530 - 590, in increment of 5)
 108 cells: XMTD3xxxCBDBW (xxx = 480 - 530, in increment of 5)
 108 cells: XMTD3xxxCBDBB (xxx = 480 - 530, in increment of 5)
 108 cells: XMTD3xxxCBDFW (xxx = 480 - 530, in increment of 5)
 108 cells: XMTD3xxxCBDFBW (xxx = 480 - 530, in increment of 5)
 108 cells: XMTD5xxxCBDBW (xxx = 480 - 530, in increment of 5)
 108 cells: XMTD5xxxCBDBB (xxx = 480 - 530, in increment of 5)
 108 cells: XMTD5xxxCBDFW (xxx = 480 - 530, in increment of 5)
 108 cells: XMTD5xxxCBDFBW (xxx = 480 - 530, in increment of 5)
 96 cells: XMTC3xxxCBDBW (xxx = 425 - 475, in increment of 5)
 96 cells: XMTC3xxxCBDBB (xxx = 425 - 475, in increment of 5)
 96 cells: XMTC3xxxCBDFW (xxx = 425 - 475, in increment of 5)
 96 cells: XMTC3xxxCBDFBW (xxx = 425 - 475, in increment of 5)
 96 cells: XMTC5xxxCBDBW (xxx = 425 - 475, in increment of 5)
 96 cells: XMTC5xxxCBDBB (xxx = 425 - 475, in increment of 5)
 96 cells: XMTC5xxxCBDFW (xxx = 425 - 475, in increment of 5)
 96 cells: XMTC5xxxCBDFBW (xxx = 425 - 475, in increment of 5)
 Remark: xxx indicates rated output power generated from front side under STC

Maximum system voltage: 1500V
 Maximum overcurrent protection rating: 30A
 Electrical protection class: Class II
 Pollution degree: 1

Essen, 2026-10-15

Certification Body - Consumer Products

TÜV NORD CERT GmbH

Am TÜV 1, 45307 Essen, Germany

tuev-nord-cert.de | prodcert@tuev-nord.de

98th percentile module operating temperature (T₉₈): 70°C

Module types:

Double Glass PV Modules with 210 x 105 mm TOPCon Bifacial Mono Solar Cells:

132 cells: XMTF4xxxCBDW (xxx = 700 - 730, in increment of 5)

132 cells: XMTF4xxxCBDBW (xxx = 700 - 730, in increment of 5)

132 cells: XMTF4xxxCBDFW (xxx = 700 - 730, in increment of 5)

132 cells: XMTF4xxxCBDFB (xxx = 700 - 730, in increment of 5)

Remark: xxx indicates rated output power generated from front side under STC

Maximum system voltage: 1500V

Maximum overcurrent protection rating: 30A

Electrical protection class: Class II

Pollution degree: 1

98th percentile module operating temperature (T₉₈): 70°C

Module types:

Double Glass PV Modules with 184 x 107/107.65 mm TOPCon Bifacial Mono Solar Cells:

132 cells: XMTF9xxxCBDW (xxx = 585 - 670, in increment of 5)

132 cells: XMTF9xxxCBDBW (xxx = 585 - 670, in increment of 5)

132 cells: XMTF9xxxCBDBB (xxx = 585 - 670, in increment of 5)

132 cells: XMTF9xxxCBDFW (xxx = 585 - 670, in increment of 5)

132 cells: XMTF9xxxCBDFB (xxx = 585 - 670, in increment of 5)

132 cells: XMTF6xxxCBDW (xxx = 585 - 670, in increment of 5)

132 cells: XMTF6xxxCBDBW (xxx = 585 - 670, in increment of 5)

132 cells: XMTF6xxxCBDBB (xxx = 585 - 670, in increment of 5)

132 cells: XMTF6xxxCBDFW (xxx = 585 - 670, in increment of 5)

132 cells: XMTF6xxxCBDFB (xxx = 585 - 670, in increment of 5)

132 cells: XMTF6xxxCBDFB (xxx = 585 - 670, in increment of 5)

132 cells: XMTF6xxxCBDFB (xxx = 585 - 670, in increment of 5)

132 cells: XMTF6xxxCBDFB (xxx = 585 - 670, in increment of 5)

132 cells: XMTF6xxxCBDFB (xxx = 585 - 670, in increment of 5)

132 cells: XMTF6xxxCBDFB (xxx = 585 - 670, in increment of 5)

132 cells: XMTF6xxxCBDFB (xxx = 585 - 670, in increment of 5)

132 cells: XMTF6xxxCBDFB (xxx = 585 - 670, in increment of 5)

132 cells: XMTF6xxxCBDFB (xxx = 585 - 670, in increment of 5)

132 cells: XMTF6xxxCBDFB (xxx = 585 - 670, in increment of 5)

132 cells: XMTF6xxxCBDFB (xxx = 585 - 670, in increment of 5)

132 cells: XMTF6xxxCBDFB (xxx = 585 - 670, in increment of 5)

132 cells: XMTF6xxxCBDFB (xxx = 585 - 670, in increment of 5)

132 cells: XMTF6xxxCBDFB (xxx = 585 - 670, in increment of 5)

132 cells: XMTF6xxxCBDFB (xxx = 585 - 670, in increment of 5)

132 cells: XMTF6xxxCBDFB (xxx = 585 - 670, in increment of 5)

132 cells: XMTF6xxxCBDFB (xxx = 585 - 670, in increment of 5)

132 cells: XMTF6xxxCBDFB (xxx = 585 - 670, in increment of 5)

132 cells: XMTF6xxxCBDFB (xxx = 585 - 670, in increment of 5)

132 cells: XMTF6xxxCBDFB (xxx = 585 - 670, in increment of 5)

132 cells: XMTF6xxxCBDFB (xxx = 585 - 670, in increment of 5)

132 cells: XMTF6xxxCBDFB (xxx = 585 - 670, in increment of 5)

132 cells: XMTF6xxxCBDFB (xxx = 585 - 670, in increment of 5)

132 cells: XMTF6xxxCBDFB (xxx = 585 - 670, in increment of 5)

132 cells: XMTF6xxxCBDFB (xxx = 585 - 670, in increment of 5)

132 cells: XMTF6xxxCBDFB (xxx = 585 - 670, in increment of 5)

132 cells: XMTF6xxxCBDFB (xxx = 585 - 670, in increment of 5)

132 cells: XMTF6xxxCBDFB (xxx = 585 - 670, in increment of 5)

132 cells: XMTF6xxxCBDFB (xxx = 585 - 670, in increment of 5)

132 cells: XMTF6xxxCBDFB (xxx = 585 - 670, in increment of 5)

132 cells: XMTF6xxxCBDFB (xxx = 585 - 670, in increment of 5)

132 cells: XMTF6xxxCBDFB (xxx = 585 - 670, in increment of 5)

132 cells: XMTF6xxxCBDFB (xxx = 585 - 670, in increment of 5)

132 cells: XMTF6xxxCBDFB (xxx = 585 - 670, in increment of 5)

132 cells: XMTF6xxxCBDFB (xxx = 585 - 670, in increment of 5)

132 cells: XMTF6xxxCBDFB (xxx = 585 - 670, in increment of 5)

132 cells: XMTF6xxxCBDFB (xxx = 585 - 670, in increment of 5)

Essen, 2026-10-15

Certification Body - Consumer Products

TÜV NORD CERT GmbH

Am TÜV 1, 45307 Essen, Germany

tuev-nord-cert.de | prodcert@tuev-nord.de

108 cells: XMTD9xxxCBDFW (xxx = 480 - 545, in increment of 5)
 108 cells: XMTD9xxxCBDFBW (xxx = 480 - 545, in increment of 5)
 108 cells: XMTD9xxxCBDFBB (xxx = 480 - 545, in increment of 5)
 108 cells: XMTD6xxxCBDW (xxx = 480 - 545, in increment of 5)
 108 cells: XMTD6xxxCBDBW (xxx = 480 - 545, in increment of 5)
 108 cells: XMTD6xxxCBDBB (xxx = 480 - 545, in increment of 5)
 108 cells: XMTD6xxxCBDFW (xxx = 480 - 545, in increment of 5)
 108 cells: XMTD6xxxCBDFBW (xxx = 480 - 545, in increment of 5)
 108 cells: XMTD6xxxCBDFBB (xxx = 480 - 545, in increment of 5)
 96 cells: XMTC9xxxCBDW (xxx = 425 - 485, in increment of 5)
 96 cells: XMTC9xxxCBDBW (xxx = 425 - 485, in increment of 5)
 96 cells: XMHCTV3xxxBFDGBW+H (xxx = 425 - 485, in increment of 5)
 96 cells: XMTC9xxxCBDBB (xxx = 425 - 485, in increment of 5)
 96 cells: XMTC9xxxCBDFW (xxx = 425 - 485, in increment of 5)
 96 cells: XMTC9xxxCBDFBW (xxx = 425 - 485, in increment of 5)
 96 cells: XMTC9xxxCBDFBB (xxx = 425 - 485, in increment of 5)
 96 cells: XMTC6xxxCBDW (xxx = 425 - 485, in increment of 5)
 96 cells: XMTC6xxxCBDBW (xxx = 425 - 485, in increment of 5)
 96 cells: XMTC6xxxCBDBB (xxx = 425 - 485, in increment of 5)
 96 cells: XMTC6xxxCBDFW (xxx = 425 - 485, in increment of 5)
 96 cells: XMTC6xxxCBDFBW (xxx = 425 - 485, in increment of 5)
 96 cells: XMTC6xxxCBDFBB (xxx = 425 - 485, in increment of 5)
 Remark: xxx indicates rated output power generated from front side under STC

Maximum system voltage: 1500V
 Maximum overcurrent protection rating: 30A
 Electrical protection class: Class II
 Pollution degree: 1
 98th percentile module operating temperature (T₉₈): 70°C

Module types: **Double Glass PV Modules with 182 x 105 mm TOPCon Bifacial Mono Solar Cells and Colorful Glass:**
 96 cells: XMTC3xxxCBD(RR/CC/TT/AA/MM/LL/OO/SS/II)-xxxW (xxx = 315 - 465, in increment of 5)
 96 cells: XMTC3xxxCBDF(RR/CC/TT/AA/MM/LL/OO/SS/II)-xxxW (xxx = 315 - 465, in increment of 5)
 Remark: xxx indicates rated output power generated from front side under STC

Maximum system voltage: 1500V
 Maximum overcurrent protection rating: 30A
 Electrical protection class: Class II
 Pollution degree: 1
 98th percentile module operating temperature (T₉₈): 70°C

Essen, 2026-10-15

Certification Body - Consumer Products

TÜV NORD CERT GmbH

Am TÜV 1, 45307 Essen, Germany

tuev-nord-cert.de | prodcert@tuev-nord.de

Module types:

Double Glass PV Modules with 184 x 107/107.65 mm TOPCon Bifacial Mono Solar Cells and Colorful Glass:

108 cells: XMTD9xxxCBD(RR/CC/TT/AA/MM/LL/OO/SS/II)-xxxW (xxx = 360 - 545, in increment of 5)

108 cells: XMTD9xxxCBDF(RR/CC/TT/AA/MM/LL/OO/SS/II)-xxxW (xxx = 360 - 545, in increment of 5)

108 cells: XMTD6xxxCBD(RR/CC/TT/AA/MM/LL/OO/SS/II)-xxxW (xxx = 360 - 545, in increment of 5)

108 cells: XMTD6xxxCBDF(RR/CC/TT/AA/MM/LL/OO/SS/II)-xxxW (xxx = 360 - 545, in increment of 5)

96 cells: XMTC9xxxCBD(RR/CC/TT/AA/MM/LL/OO/SS/II)-xxxW (xxx = 320 - 485, in increment of 5)

96 cells: XMTC9xxxCBDF(RR/CC/TT/AA/MM/LL/OO/SS/II)-xxxW (xxx = 320 - 485, in increment of 5)

96 cells: XMTC6xxxCBD(RR/CC/TT/AA/MM/LL/OO/SS/II)-xxxW (xxx = 320 - 485, in increment of 5)

96 cells: XMTC6xxxCBDF(RR/CC/TT/AA/MM/LL/OO/SS/II)-xxxW (xxx = 320 - 485, in increment of 5)

Remark: xxx indicates rated output power generated from front side under STC

Maximum system voltage: 1500V

Maximum overcurrent protection rating: 30A

Electrical protection class: Class II

Pollution degree: 1

98th percentile module operating temperature (T₉₈): 70°C

Remark:

For detailed product information, please refer to CDF (Constructional Data Form) with the same file no.

Essen, 2026-10-15

Certification Body - Consumer Products

TÜV NORD CERT GmbH

Am TÜV 1, 45307 Essen, Germany

tuev-nord-cert.de | prodcert@tuev-nord.de